



# HITO CHEMICAL

## Material Safety Data Sheet

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: H-202  
Chemical name: H-202 Methyl Hydrogen Silicone Fluid  
MANUFACTURED BY: JIANGXI HITO CHEMICAL CO.,LTD  
NO 6,TIANHONG ROAD,XINGHUO INDUSTRY ZONE,  
JIUJIANG CITY, JIANGXI PROVINCE,CHINA  
POST CODE: 330319  
Emergency telephone number: +86-792-3170318

### SECTION 2 – COMPOSITION, INFORMATION ON INGREDIENTS

<u>CAS NO.</u>	<u>Component Name</u>
63148-57-2	Methylhydrogen-Dimethylsiloxane siloxane

### SECTION 3 – HAZARDS IDENTIFICATION

<b>Eye</b>	Direct contact may cause temporary redness and discomfort.
<b>Skin</b>	No significant irritation expected from a single short-term exposure.
<b>Inhalation</b>	No significant effects expected from a single short-term exposure.
<b>Oral</b>	Low ingestion hazard in normal use

### SECTION 4 - FIRST AID MEASURES

<b>Eye</b>	Immediately flush with water.
<b>Skin</b>	No first aid should be needed.
<b>Inhalation</b>	No first aid should be needed.
<b>Oral</b>	No first aid should be needed.
<b>Comments</b>	Treat symptomatically.

### SECTION 5 - FIRE FIGHTING MEASURES

<b>Flash point</b>	> 85°C
<b>Autoignition temperture</b>	Not determined.
<b>Flammability limits in air</b>	Not determined.
<b>Extinguishing media</b>	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide(CO <sub>2</sub> ), dry chemical or water spray. Water can

be used to cool fire exposed containers.

**Fire Fighting Measures**

Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

**Unusual fire hazards**

None.

**Hazardous decomposition products**

Silicon dioxide. Carbon oxides and traces of incompletely burned carbon compounds.  
Formaldehyde. Hydrogen.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**Containment/Clean up**

Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Section 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Recovered material should be stored in a vented container. Clean up remaining materials from spill with suitable absorbent. Clean area as appropriate since some silicone materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and materials and items employed in the cleanup of releases.

**SECTION 7 - HANDLING AND STORAGE**

Use with adequate ventilation. Avoid eye contact.

Static electricity will accumulate and may ignite vapors. Prevent a possible fire hazard by bonding and grounding or inert gas purge. Keep container closed and away from heat, sparks and flame. Product evolves minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Do not store in glass containers which may shatter due to pressure build up. Clogged container vents may increase pressure build up. Keep container closed and store away from water or moisture.

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

**Component Exposure Limits** There are no components with workplace exposure limits.

### Personal Protective Equipment

**Eyes** Use proper protection-safety glasses as a minimum.

**Skin** Washing at mealtime and end of shift is adequate.

**Suitable gloves** No special protection needed.

**Inhalation** No respiratory protection should be needed.

**Suitable respirator** None should be needed.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical form</b>	Liquid
<b>Color</b>	Colorless
<b>Odor</b>	Odorless
<b>Specific gravity at 25°C</b>	0.9~1.0
<b>Viscosity</b>	20-300cSt
<b>Refractive index at 25°C</b>	1.390~1.400
<b>Freezing/Melting point</b>	Not determined.
<b>Boiling point</b>	>150°C
<b>Vapor pressure at 25°C</b>	Not determined.
<b>Vapor density</b>	Not determined.
<b>Solubility in water</b>	Not determined.
<b>PH</b>	6.0-7.0
<b>Volatile content</b>	<9.0%

**Note** The above information is not intended for use in preparing product specifications.

## SECTION 10 - STABILITY AND REACTIVITY

**Chemical Stability** Stable.

**Conditions to Avoid** None.

**Materials to Avoid** Oxidizing material can cause a reaction. Water, alcohols, acidic or basic materials, and many metals or metallic compounds, when in contact with product, liberate flammable hydrogen gas, which can form explosive mixtures in air.

**Hazardous Polymerization** Will not occur.

## SECTION 11 - TOXICOLOGICAL INFORMATION

No known applicable information

## SECTION 12 - ECOLOGICAL INFORMATION

**Ecotoxicological information** No data at this time.

**Chemical fate information** No data at this time

## SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations

## SECTION 14 - TRANSPORT INFORMATION

### **DOT Classification:**

This product is not regulated by DOT.

**Freight description road:** OIL, O/T PETROLEUM, LUBRICATING, NOIBN

**IMDG Classification:** This product is not regulated by IMDG.

## SECTION 15 - REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

### **EPA SARA Title III Chemical Listings**

#### **Section 302 Extremely Hazardous Substances:**

None.

#### **Section 304 CERCLA Hazardous Substances:**

None.

#### **Section 312 Hazard Class:**

Acute: No

Chronic: No

Fire: No

Pressure: No

Reactive: No

#### **Section 313 Toxic Chemicals:**

None present or none present in regulated quantities.

#### **New Jersey**

CAS Number

Component Name

63148-57-2

Methylhydrogen-Dimethylsiloxane siloxane

## SECTION 16 - ADDITIONAL INFORMATION

The above information is usual data and not be regarded as technically standard when using, which is according as regulate of environment and transport. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular proposes.