



JIANGXI HITO CHEMICAL CO.,LTD

No 6 Tianhong road,Xinghuo

industry zone,Yongxiu,

Jiujiang,Jiangxi province,China

(86)792-3170318(Tel) (86) 792-3170355 (Fax)

TECHNICAL DATA SHEET

H-245
Substrate wetting agent

DESCRIPTION

H-245 Substrate wetting agent

Can be used for water-based formulations, with good recoatability, can significantly improve wettability timber wood hole (in the wood coatings and thin coating), it can promote the flow of additional action, with low foaming.

TYPICAL PROPERTIES

Appearance	Transparent liquid
Viscosity	30-50 mPas
Active content	100%
Density	1.04 g/cm ³

USES AND APPLICATION

Application system: water-based, solvent-based and solvent-free systems

Dosage: Recommended dosage of 0.2 to 1.5% of the total formulation

SAFETY

Before handling, read the Material Safety Data Sheet and container label for safe use, physical and health hazard information.

STORAGE AND SHELF LIFE

After sealing packaging products stored in a cool, dry place

H-245 Substrate wetting agent has a shelf life of 36 months from date of manufacture.

PACKAGING

H-245 Substrate wetting agent is available in 200L drum and 1000L IBC or others.

LEGAL DISCLAIMER

Hito chemical believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Hito Chemical, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that

are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.



is a registered trademark of Hito chemical , China.